




Brand:



mod: **KfIV focus IV (Bulletproof)**

Open field Ballistic & Blast tests: <http://www.youtube.com/watch?v=hW08BIYixjE>
<http://www.youtube.com/watch?v=2Hj0zmF5RA8>


Country of origin: Greece

Dimensions: 1,50mX1,50mX2,25m (H)
20' sea-container compatible (up to 3 pcs)

Weight: 3.000 kgs (application and configuration dependent)

Crew: Up to 2.

Calibres and types of ammunition that the sentry resists:



- | | |
|---------------------------|-------------------------------------|
| Level IV | Level IV + (plus) (optional) |
| .30 cal (7.62 x 51 mm) AP | .50 cal (12,7 x 99 mm) Ball |
| 5.56 x 45 mm (NATO) | .338 cal (8,60 x 70 mm) Ball |
| .45 cal | .30 cal (7.62 x 51 mm) AP |
| .40 cal | 5.56 x 45 mm (NATO) |
| 9 mm | .45 cal |
| | .40 cal |
| | 9 mm |
| | US-S 515P SLUG |
| | 12 GAUGE |

Walls, roof and floor Ballistic proof to Level IV (NIJ) - Standard-0108.01.

Doors, windows and gun ports 1 bullet proof door c/w Level IV (NS) window 45cmX64cm.
3 bullet proof windows Level IV (NS) 106cmX79cm (non-opening).
Half-size Level IV (NS) windows are also available.
All windows are available with tinted or reflective splinter-free glass.
3 Gun ports. (fast open type) 15cm x 10cm standard size. Bullet proof to Level IV when closed.

Physical ventilation: 2 ventilation zones, blast and ballistically fully protected.

Electrical: 220 V - 50 HZ
Main fuseboard.
2 triple sockets + 1 roof light.
A/C line.

Power Requirements: 5,0 Kw.

Accessories included: A/C 9.000 btu heater-cooler Heat output 4 kw
Beverage fridge 12 L.
2 Roof mounted search/flood lights adjustable from inside.
1st aid kit.
1 fire exstinguisher - 2kgs
1 chair
1 communication Interphone.
Emergency rechargeable torch,

NBC Protection (included): NBC Gas mask (specifications NATO AC/225/Pannel VII/D 103

Optional accessories: Canopy,
CBRNe air filtration system,
Movement detection system,
Infra red night vision system,
Sound detection system,
P.A. system,
Specialised communication packs,

Emergency evacuation facility: Sentry features emergency evacuation facility according to European regulation: 89/655/EOK

(All features subject to changes in design and further technical development.)